



| | |
|------------------------------|--|
| Title of Change: | MC74HC1GXX Family Datasheet updates per FPCN22038X. |
| Effective date: | 26 June 2019 |
| Contact information: | Contact your local ON Semiconductor Sales Office or <david.manley@onsemi.com> |
| Type of notification: | This Product Bulletin is for notification purposes only. ON Semiconductor will proceed with implementation of this change upon publication of this Product Bulletin. |
| Change Category: | <input type="checkbox"/> Wafer Fab <input type="checkbox"/> Assembly Change <input type="checkbox"/> Test Change <input checked="" type="checkbox"/> Other <u>Datasheet Change</u> |

Change Sub-Category(s):

- ☐ Manufacturing Site Addition
 ☐ Material Change
 ☒ Datasheet/Product Doc change
- ☐ Manufacturing Site Transfer
 ☐ Product specific change
 ☐ Shipping/Packaging/Marking
- ☐ Manufacturing Process Change
 ☐ Other: _____

Sites Affected:
 ON Semiconductor Sites:
None

 External Foundry/Subcon Sites:
None
Description and Purpose:

This PB is issued to notify customers of datasheet changes for the MC74HC1G family per FPCN22038X.

Provided here are comparison between the new and old datasheets regarding changing specifications and/or specification conditions.

- Areas of change are circled red.
- Items from the old datasheet that will be changed are highlighted red.
- The corresponding value on the new datasheet is highlighted in green.
- Areas of change circled in yellow are changes that were found to be needed after the PCN

There will be other changes that represent a cleanup and standardization to the datasheet to represent a family oriented specification format. These changes will include forms of the following:

- Correction of clerical errors such as spelling.
- Formatting to create family standards.
- Addition of new package types and possible removal of packages no longer available.
- Standardization of the switching waveforms test circuit figures.
- Formatting of the Device ordering information to provide more information to the customer regarding marking and Pin 1 orientation in tape or reel.
- **Max voltage rating changed from 7.0 Volts to 6.5 Volts (Excluding Automotive Devices)**
- **Thermal resistance and Power Dissipation adjusted to reflect new die.**
- **Electrostatic Discharge/Latch-up adjusted to reflect new JEDEC Standard.**

Existing datasheet

| MAXIMUM RATINGS | | | |
|----------------------|---|---|----------------------|
| Symbol | Parameter | Value | Unit |
| V _{CC} | DC Supply Voltage | -0.5 to +7.0 | V |
| V _{IN} | DC Input Voltage | -0.5 to V _{CC} + 0.5 | V |
| V _{OUT} | DC Output Voltage | -0.5 to V _{CC} + 0.5 | V |
| I _{IK} | DC Input Diode Current | ±20 | mA |
| I _{OK} | DC Output Diode Current | ±20 | mA |
| I _{OUT} | DC Output Sink Current | ±12.5 | mA |
| I _{CC} | DC Supply Current per Supply Pin | ±25 | mA |
| T _{STG} | Storage Temperature Range | -65 to +150 | °C |
| T _L | Lead Temperature, 1 mm from Case for 10 Seconds | 260 | °C |
| T _J | Junction Temperature Under Bias | +150 | °C |
| θ _{JA} | Thermal Resistance | 350 230 | °C/W |
| P _D | Power Dissipation in Still Air at 85°C | 150 200 | mW |
| MSL | Moisture Sensitivity | Level 1 | |
| F _R | Flammability Rating | Oxygen Index: 28 to 34 | UL 94 V-0 @ 0.125 in |
| V _{ESD} | ESD Withstand Voltage | > 2000 > 200 N/A | V |
| I _{LATCHUP} | Latchup Performance | Above V _{CC} and Below GND at 125°C (Note 5) | ±500 mA |

New

| MAXIMUM RATINGS | | | | |
|-------------------------------------|---|--|------------------------------|------|
| Symbol | Parameter | | Value | Unit |
| V _{CC} | DC Supply Voltage | SC-88A (NLV), TSOP-5 SC-88A, SC-74A | -0.5 to +7.0 -0.5 to +6.5 | V |
| V _{IN} | DC Input Voltage | | -0.5 to V _{CC} +0.5 | V |
| V _{OUT} | DC Output Voltage | | -0.5 to V _{CC} +0.5 | V |
| I _{IK} | DC Input Diode Current | | ±20 | mA |
| I _{OK} | DC Output Diode Current | | ±20 | mA |
| I _{OUT} | DC Output Source/Sink Current | | ±12.5 | mA |
| I _{CC} or I _{QND} | DC Supply Current per Supply Pin or Ground Pin | | ±25 | mA |
| T _{STG} | Storage Temperature Range | | -65 to +150 | °C |
| T _L | Lead Temperature, 1 mm from Case for 10 Seconds | | 260 | °C |
| T _J | Junction Temperature Under Bias | | +150 | °C |
| θ _{JA} | Thermal Resistance (Note 1) | SC70-5/SC-88A/SOT-353 SOT23-5/TSOP-5/SC59-5 SC-74A | 659 555 555 | °C/W |
| P _D | Power Dissipation in Still Air at 85°C | SC70-5/SC-88A/SOT-353 SOT23-5/TSOP-5/SC59-5 SC-74A | 190 225 225 | mW |
| MSL | Moisture Sensitivity | | Level 1 | |
| F _R | Flammability Rating | Oxygen Index: 28 to 34 | UL 94 V-0 @ 0.125 in | |
| V _{ESD} | ESD Withstand Voltage (Note 2) | Human Body Model Charged Device Model | 2000 1000 | V |
| I _{LATCHUP} | Latchup Performance (Note 3) | SC-88A (NLV), SOT-23 SC-88A, SC-74A | ±500 ±100 | mA |



- Input Rise and fall time adjusted to reflect new process.

Existing datasheet

RECOMMENDED OPERATING CONDITIONS

| Symbol | Parameter | Min | Max | Unit |
|------------|-----------------------------|---|---------------------------|------|
| V_{CC} | DC Supply Voltage | 2.0 | 6.0 | V |
| V_{IN} | DC Input Voltage | 0.0 | V_{CC} | V |
| V_{OUT} | DC Output Voltage | 0.0 | V_{CC} | V |
| T_A | Operating Temperature Range | -55 | +125 | °C |
| t_r, t_f | Input Rise and Fall Time | $V_{CC} = 2.0$ V 0 $V_{CC} = 3.0$ V 0 $V_{CC} = 4.5$ V 0 $V_{CC} = 6.0$ V | 1000 600 500 400 | ns |

New

RECOMMENDED OPERATING CONDITIONS

| Symbol | Parameter | Min | Max | Unit |
|------------|-----------------------------|---|---------------------------|------|
| V_{CC} | DC Supply Voltage | 2.0 | 6.0 | V |
| V_{IN} | DC Input Voltage | 0.0 | V_{CC} | V |
| V_{OUT} | DC Output Voltage | 0.0 | V_{CC} | V |
| T_A | Operating Temperature Range | -55 | +125 | °C |
| t_r, t_f | Input Rise and Fall Time | SC-88A (NLV), TSOP-5 $V_{CC} = 2.0$ V 0 $V_{CC} = 3.0$ V 0 $V_{CC} = 4.5$ V 0 $V_{CC} = 6.0$ V | 1000 600 500 400 | ns/V |
| | Input Rise and Fall Time | SC-88A, SC-74A $V_{CC} = 1.65$ V to 1.95 V 0 $V_{CC} = 2.3$ V to 2.7 V 0 $V_{CC} = 3.0$ V to 3.6 V 0 $V_{CC} = 4.5$ V to 6.0 V | 20 20 10 5 | |

- Positive Threshold Voltage adjusted to remove minimum limits.
- Negative Threshold Voltage adjusted to remove maximum limits.

Existing datasheet

DC ELECTRICAL CHARACTERISTICS

| Symbol | Parameter | Test Conditions | V_{CC} (V) | $T_A = 25^\circ\text{C}$ | $T_A \leq 85^\circ\text{C}$ | $-55^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$ | Unit |
|----------|-----------------------------------|---|--------------|--------------------------|-----------------------------|---|---------------|
| V_{TH} | Positive Threshold Voltage | | 3.0 | 1.85 | 2.0 | 2.20 | V |
| | | | 4.5 | 2.85 | 3.0 | 3.15 | |
| | | | 5.5 | 3.50 | 3.6 | 3.85 | |
| V_{TL} | Negative Threshold Voltage | | 3.0 | 0.9 | 1.5 | 1.85 | V |
| | | | 4.5 | 1.35 | 2.3 | 2.46 | |
| | | | 5.5 | 1.65 | 2.9 | 3.05 | |
| V_H | Hysteresis Voltage | | 3.0 | 0.30 | 0.57 | 1.20 | V |
| | | | 4.5 | 0.40 | 0.67 | 1.40 | |
| | | | 5.5 | 0.50 | 0.74 | 1.60 | |
| V_{OH} | Minimum High-Level Output Voltage | $V_{IN} = V_{TH}$ or V_{IL} $I_{OH} = -20 \mu\text{A}$ | 3.0 | 1.9 | 2.0 | 1.9 | V |
| | | | 4.5 | 2.9 | 3.0 | 2.9 | |
| | | | 5.5 | 4.4 | 4.5 | 4.4 | |
| | | | 6.0 | 5.9 | 6.0 | 5.9 | |
| V_{OL} | Maximum Low-Level Output Voltage | $V_{IN} \leq V_{TL} - \text{Min}$ $I_{OL} = -2.6 \text{ mA}$ | 4.5 | 4.18 | 4.31 | 4.13 | V |
| | | | 6.0 | 5.68 | 5.80 | 5.63 | |
| | | $V_{IN} \geq V_{TH} + \text{Max}$ $I_{OL} = 20 \mu\text{A}$ | 2.0 | 0.0 | 0.1 | 0.1 | |
| | | | 3.0 | 0.0 | 0.1 | 0.1 | |
| | | | 4.5 | 0.0 | 0.1 | 0.1 | |
| | | | 6.0 | 0.0 | 0.1 | 0.1 | |
| | | $V_{IN} = V_{TH}$ or V_{IL} $I_{OL} = 2 \text{ mA}$ $I_{OL} = 2.6 \text{ mA}$ | 4.5 | 0.17 | 0.26 | 0.33 | 0.40 |
| | | | 6.0 | 0.18 | 0.26 | 0.33 | |
| I_{IN} | Maximum Input Leakage Current | $V_{IN} = 6.0 \text{ V or GND}$ | 6.0 | | ± 0.1 | ± 1.0 | μA |
| I_{CC} | Maximum Quiescent Supply Current | $V_{IN} = V_{CC}$ or GND | 6.0 | | 1.0 | 10 | μA |

New

DC ELECTRICAL CHARACTERISTICS

| Symbol | Parameter | Test Conditions | V_{CC} (V) | $T_A = 25^\circ\text{C}$ | $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ | $-55^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$ | Unit |
|----------|----------------------------|---|--------------|--------------------------|--|---|---------------|
| V_{TH} | Positive Threshold Voltage | | 3.0 | 2.0 | 2.20 | 2.20 | V |
| | | | 4.5 | 3.0 | 3.15 | 3.15 | |
| | | | 5.5 | 3.6 | 3.65 | 3.65 | |
| V_{TL} | Negative Threshold Voltage | | 3.0 | 0.9 | 1.5 | 0.9 | V |
| | | | 4.5 | 1.35 | 2.3 | 1.35 | |
| | | | 5.5 | 1.65 | 2.9 | 1.65 | |
| V_H | Hysteresis Voltage | | 3.0 | 0.30 | 0.57 | 1.20 | V |
| | | | 4.5 | 0.40 | 0.67 | 1.40 | |
| | | | 5.5 | 0.50 | 0.74 | 1.60 | |
| V_{OH} | High-Level Output Voltage | $V_{IN} = V_{TH}$ or V_{IL} $I_{OH} = -20 \mu\text{A}$ | 2.0 | 1.9 | 2.0 | 1.9 | V |
| | | | 3.0 | 2.9 | 3.0 | 2.9 | |
| | | | 4.5 | 4.4 | 4.5 | 4.4 | |
| | | | 6.0 | 5.9 | 6.0 | 5.9 | |
| | | $V_{IN} = V_{TH}$ or V_{IL} $I_{OH} = -2 \text{ mA}$ $I_{OH} = -2.6 \text{ mA}$ | 4.5 | 4.18 | 4.31 | 4.13 | 4.08 |
| | | | 6.0 | 5.68 | 5.80 | 5.63 | 5.58 |
| V_{OL} | Low-Level Output Voltage | $V_{IN} \leq V_{TL} - \text{Min}$ $I_{OL} = 20 \mu\text{A}$ | 2.0 | 0.0 | 0.1 | 0.1 | V |
| | | | 3.0 | 0.0 | 0.1 | 0.1 | |
| | | | 4.5 | 0.0 | 0.1 | 0.1 | |
| | | | 6.0 | 0.0 | 0.1 | 0.1 | |
| | | $V_{IN} = V_{TH}$ or V_{IL} $I_{OL} = 2 \text{ mA}$ $I_{OL} = 2.6 \text{ mA}$ | 4.5 | 0.17 | 0.26 | 0.33 | 0.40 |
| | | | 6.0 | 0.18 | 0.26 | 0.33 | 0.40 |
| I_{IN} | Input Leakage Current | $V_{IN} = 6.0 \text{ V or GND}$ | 6.0 | | ± 0.1 | ± 1.0 | μA |
| I_{CC} | Quiescent Supply Current | $V_{IN} = V_{CC}$ or GND | 6.0 | | 1.0 | 10 | μA |

List of Affected Parts:

Note: Only the standard (off the shelf) part numbers are listed in the parts list. Any custom parts affected by this PCN are shown in the customer specific PCN addendum in the PCN email notification, or on the [PCN Customized Portal](#).

MC74HC1G00DFT1G

MC74HC1G04DFT2G

MC74HC1G32DFT1G

MC74HC1G00DFT2G

MC74HC1G08DFT1G

MC74HC1G32DFT2G

MC74HC1G02DFT2G

MC74HC1G08DFT2G

MC74HC1GU04DFT1G

MC74HC1G04DFT1G

MC74HC1G14DFT1G

MC74HC1GU04DFT2G

MC74HC1G14DFT2G

Japanese translation of the notification starts here.
通知の日本語訳はここから始まります。

Note: *The Japanese version is for reference only. In case of any differences between the English and Japanese version, the English version shall control.*

注：日本語版は参照用です。英語版と日本語版の違いがある場合は、英語版が優先されます。



| | | |
|-----------|---|------------------------|
| 変更件名: | MC74HC1GXX ファミリー FPCN22038X についてのデータシートの更新 | |
| 発効日: | 26 June 2019 | |
| 連絡先情報: | 現地のオン・セミコンダクター営業所または <david.manley@onsemi.com>にお問い合わせください。 | |
| 通知種別: | 本製品速報は通知目的のみのものです。オン・セミコンダクターは本製品速報の発行により本変更を実行します。 | |
| 変更カテゴリ: | <input type="checkbox"/> ウェハファブの変更 <input type="checkbox"/> アセンブリの変更 <input type="checkbox"/> 試験の変更 <input checked="" type="checkbox"/> その他 <u>データシートの変更</u> | |
| 変更サブカテゴリ: | <input type="checkbox"/> 製造拠点の追加 <input type="checkbox"/> 材料の変更 <input checked="" type="checkbox"/> データシート/製品資料の変更 <input type="checkbox"/> 製造拠点の移転 <input type="checkbox"/> 製品仕様の変更 <input type="checkbox"/> 出荷/パッケージング/表記 <input type="checkbox"/> その他: _____ | |
| 影響を受ける拠点: | オン・セミコンダクター拠点: なし | 外部製造工場 / 下請業者拠点: なし |

説明および目的:

本 PB は、MC74HC1G ファミリー FPCN22038X についてのデータシートの変更をお客様にお知らせするものです。

仕様および/または仕様条件の変更に関する新旧データシート間での比較を以下に示します。

- 変更箇所は赤色の丸で囲まれています。
- 旧データシートから変更される項目は赤色でハイライトされています。
- 新データシートで対応する値は緑色でハイライトされています。
- 黄色の丸で囲んだ変更箇所は PCN の後に変更が必要であることがわかったものです

他にも、ファミリーに合わせて仕様フォーマットを表現するためにデータシートの整理と標準化をしたことによる変更があります。これらの変更は、以下のよう形で行われます。

- スペルなどの事務的なミスの訂正。
- ファミリーの標準を作成するための書式設定。
- 新しいパッケージタイプの追加、および入手できなくなったパッケージの削除見込み。
- 波形切り替え試験回路図の標準化。
- マーキング、およびテープまたはリールでのピン 1 の向きに関して、お客様にさらに情報を提供するための、デバイス注文情報の書式設定。
- 最大定格電圧が 7.0V から 6.5V に変更(車載デバイスを除く)
- 新規のダイを反映するために熱抵抗とワット損を調整。
- JEDEC 新規格を反映するために静電放電/ラッチアップを調整。

Existing datasheet

| MAXIMUM RATINGS | | | |
|----------------------|---|--|----------------------|
| Symbol | Parameter | Value | Unit |
| V _{CC} | DC Supply Voltage | -0.5 to +7.0 | V |
| V _{IN} | DC Input Voltage | -0.5 to V _{CC} + 0.5 | V |
| V _{OUT} | DC Output Voltage | -0.5 to V _{CC} + 0.5 | V |
| I _{IK} | DC Input Diode Current | ±20 | mA |
| I _{OK} | DC Output Diode Current | ±20 | mA |
| I _{OUT} | DC Output Sink Current | ±12.5 | mA |
| I _{CC} | DC Supply Current per Supply Pin | ±25 | mA |
| T _{STG} | Storage Temperature Range | -65 to +150 | °C |
| T _L | Lead Temperature, 1 mm from Case for 10 Seconds | 260 | °C |
| T _J | Junction Temperature Under Bias | +150 | °C |
| θ _{JA} | Thermal Resistance | 350 230 | °C/W |
| P _D | Power Dissipation in Still Air at 85°C | 150 200 | mW |
| MSL | Moisture Sensitivity | Level 1 | |
| F _B | Flammability Rating | Oxygen Index: 28 to 34 UL 94 V-0 @ 0.125 in | |
| V _{ESD} | ESD Withstand Voltage | Human Body Model (Note 2) Machine Model (Note 3) Charged Device Model (Note 4) | >2000 >200 N/A |
| I _{LATCHUP} | Latchup Performance | Above V _{CC} and Below GND at 125°C (Note 5) | ±500 |

New

| MAXIMUM RATINGS | | | |
|-------------------------------------|---|--|--|
| Symbol | Parameter | Value | Unit |
| V _{CC} | DC Supply Voltage | SC-88A (NLV), TSOP-5 SC-88A, SC-74A | -0.5 to +7.0 -0.5 to +6.5 |
| V _{IN} | DC Input Voltage | | -0.5 to V _{CC} + 0.5 |
| V _{OUT} | DC Output Voltage | | -0.5 to V _{CC} + 0.5 |
| I _{IK} | DC Input Diode Current | | ±20 |
| I _{OK} | DC Output Diode Current | | ±20 |
| I _{OUT} | DC Output Sink Current | | ±12.5 |
| I _{CC} or I _{GND} | DC Supply Current per Supply Pin or Ground Pin | | ±25 |
| T _{STG} | Storage Temperature Range | | -65 to +150 |
| T _L | Lead Temperature, 1 mm from Case for 10 Seconds | | 260 |
| T _J | Junction Temperature Under Bias | | +150 |
| θ _{JA} | Thermal Resistance (Note 1) | SC70-5/SC-88A/SOT-353 SOT23-5/TSOP-5/SC59-5 SC-74A | 659 555 555 |
| P _D | Power Dissipation in Still Air at 85°C | SC70-5/SC-88A/SOT-353 SOT23-5/TSOP-5/SC59-5 SC-74A | 190 225 225 |
| MSL | Moisture Sensitivity | | Level 1 |
| F _B | Flammability Rating | | Oxygen Index: 28 to 34 UL 94 V-0 @ 0.125 in |
| V _{ESD} | ESD Withstand Voltage (Note 2) | Human Body Model Charged Device Model | 2000 1000 |
| I _{LATCHUP} | Latchup Performance (Note 3) | SC-88A (NLV), SOT-23 SC-88A, SC-74A | ±500 ±100 |



- 新規プロセスを反映するために入力立ち上がり/立ち下がり時間を調整。

Existing datasheet

RECOMMENDED OPERATING CONDITIONS

| Symbol | Parameter | Min | Max | Unit | |
|---------------------------------|-----------------------------|--|------------------|---------------------------|----|
| V _{CC} | DC Supply Voltage | 2.0 | 6.0 | V | |
| V _{IN} | DC Input Voltage | 0.0 | V _{CC} | V | |
| V _{OUT} | DC Output Voltage | 0.0 | V _{CC} | V | |
| T _A | Operating Temperature Range | -55 | +125 | °C | |
| t _r , t _f | Input Rise and Fall Time | V _{CC} = 2.0 V V _{CC} = 3.0 V V _{CC} = 4.5 V V _{CC} = 6.0 V | 0 0 0 0 | 1000 600 500 400 | ns |

New

RECOMMENDED OPERATING CONDITIONS

| Symbol | Parameter | Min | Max | Unit |
|------------|-----------------------------|---|----------|------|
| V_{CC} | DC Supply Voltage | 2.0 | 6.0 | V |
| V_{IN} | DC Input Voltage | 0.0 | V_{CC} | V |
| V_{OUT} | DC Output Voltage | 0.0 | V_{CC} | V |
| T_A | Operating Temperature Range | -55 | +125 | °C |
| t_r, t_f | Input Rise and Fall Time | SC-88A (NLV), TSOP-5 | | ns/V |
| | | $V_{CC} = 2.0\text{ V}$ | 0 | |
| | | $V_{CC} = 3.0\text{ V}$ | 0 | |
| | | $V_{CC} = 4.5\text{ V}$ | 0 | |
| | | $V_{CC} = 6.0\text{ V}$ | 0 | |
| | Input Rise and Fall Time | SC-88A, SC-74A | | ns |
| | | $V_{CC} = 1.65\text{ V to }1.95\text{ V}$ | 0 | |
| | | $V_{CC} = 2.3\text{ V to }2.7\text{ V}$ | 0 | |
| | | $V_{CC} = 3.0\text{ V to }3.6\text{ V}$ | 0 | |
| | | $V_{CC} = 4.5\text{ V to }6.0\text{ V}$ | 0 | |

- Positive Threshold voltage の下限を削除。
- Negative Threshold voltage の上限を削除。

Existing datasheet

DC ELECTRICAL CHARACTERISTICS

| Symbol | Parameter | Test Conditions | $T_A = 25^\circ\text{C}$ | | | | $T_A = 85^\circ\text{C}$ | | $-55^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$ | | Unit |
|----------|-----------------------------------|---|--------------------------|------|------|-----------|--------------------------|-----------|---|-----------|---------------|
| | | | V _{CC} (V) | Min | Typ | Max | Min | Max | Min | Max | |
| V_{T+} | Positive Threshold Voltage | | 3.0 | 1.85 | 2.0 | 2.20 | | 2.20 | | 2.20 | V |
| | | | 4.5 | 2.85 | 3.0 | 3.15 | | 3.15 | | 3.15 | |
| | | | 5.5 | 3.50 | 3.6 | 3.85 | | 3.85 | | 3.85 | |
| V_{T-} | Negative Threshold Voltage | | 3.0 | 0.9 | 1.5 | 1.65 | 0.9 | | 0.9 | | V |
| | | | 4.5 | 1.35 | 2.3 | 2.45 | 1.35 | | 1.35 | | |
| | | | 5.5 | 1.65 | 2.9 | 3.05 | 1.65 | | 1.65 | | |
| V_{H} | Hysteresis Voltage | | 3.0 | 0.30 | 0.57 | 1.20 | 0.30 | 1.20 | 0.30 | 1.20 | V |
| | | | 4.5 | 0.40 | 0.67 | 1.40 | 0.40 | 1.40 | 0.40 | 1.40 | |
| | | | 5.5 | 0.50 | 0.74 | 1.60 | 0.50 | 1.60 | 0.50 | 1.60 | |
| V_{OH} | Minimum High-Level Output Voltage | $V_{IN} = V_{T+}$ or V_{LH} $I_{OH} = -20\text{ }\mu\text{A}$ | 2.0 | 1.9 | 2.0 | | 1.9 | | 1.9 | | V |
| | | | 3.0 | 2.9 | 3.0 | | 2.9 | | 2.9 | | |
| | | | 4.5 | 4.4 | 4.5 | | 4.4 | | 4.4 | | |
| | | | 6.0 | 5.9 | 6.0 | | 5.9 | | 5.9 | | |
| | | $V_{IN} \leq V_{T-} - \text{Min}$ $I_{OH} = -2\text{ mA}$ $I_{OL} = -2.6\text{ mA}$ | 4.5 | 4.18 | 4.31 | | 4.13 | | 4.08 | | |
| | | | 6.0 | 5.68 | 5.80 | | 5.63 | | 5.58 | | |
| V_{OL} | Maximum Low-Level Output Voltage | $V_{IN} \geq V_{T-} + \text{Max}$ $I_{OL} = 20\text{ }\mu\text{A}$ | 2.0 | 0.0 | 0.1 | | 0.1 | | 0.1 | | V |
| | | | 3.0 | 0.0 | 0.1 | | 0.1 | | 0.1 | | |
| | | | 4.5 | 0.0 | 0.1 | | 0.1 | | 0.1 | | |
| | | | 6.0 | 0.0 | 0.1 | | 0.1 | | 0.1 | | |
| | | $V_{IN} = V_{T+}$ or V_{LH} $I_{OL} = 2\text{ mA}$ $I_{OL} = 2.6\text{ mA}$ | 4.5 | 0.17 | 0.26 | | 0.33 | | 0.40 | | |
| | | | 6.0 | 0.18 | 0.26 | | 0.33 | | 0.40 | | |
| I_{IN} | Maximum Input Leakage Current | $V_{IN} = 6.0\text{ V or GND}$ | 6.0 | | | ± 0.1 | | ± 1.0 | | ± 1.0 | μA |
| I_{CC} | Maximum Quiescent Supply Current | $V_{IN} = V_{CC}$ or GND | 6.0 | | | 1.0 | | 10 | | 40 | μA |

New

DC ELECTRICAL CHARACTERISTICS

| Symbol | Parameter | Test Conditions | V _{CC} (V) | $T_A = 25^\circ\text{C}$ | | | $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ | | $-55^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$ | | Unit |
|----------|----------------------------|---|---------------------|--------------------------|------|-----------|--|-----------|---|-----------|---------------|
| | | | | Min | Typ | Max | Min | Max | Min | Max | |
| V_{T+} | Positive Threshold Voltage | | 3.0 | - | 2.0 | 2.20 | - | 2.20 | - | 2.20 | V |
| | | | 4.5 | - | 3.0 | 3.15 | - | 3.15 | - | 3.15 | |
| | | | 5.5 | - | 3.6 | 3.85 | - | 3.85 | - | 3.85 | |
| V_{T-} | Negative Threshold Voltage | | 3.0 | 0.9 | 1.5 | | 0.9 | | 0.9 | | V |
| | | | 4.5 | 1.35 | 2.3 | | 1.35 | | 1.35 | | |
| | | | 5.5 | 1.65 | 2.9 | | 1.65 | | 1.65 | | |
| V_{H} | Hysteresis Voltage | | 3.0 | 0.30 | 0.57 | 1.20 | 0.30 | 1.20 | 0.30 | 1.20 | V |
| | | | 4.5 | 0.40 | 0.67 | 1.40 | 0.40 | 1.40 | 0.40 | 1.40 | |
| | | | 5.5 | 0.50 | 0.74 | 1.60 | 0.50 | 1.60 | 0.50 | 1.60 | |
| V_{OH} | High-Level Output Voltage | $V_{IN} = V_{T+}$ or V_{LH} $I_{OH} = -20\text{ }\mu\text{A}$ | 2.0 | 1.9 | 2.0 | | 1.9 | | 1.9 | | V |
| | | | 3.0 | 2.9 | 3.0 | | 2.9 | | 2.9 | | |
| | | | 4.5 | 4.4 | 4.5 | | 4.4 | | 4.4 | | |
| | | | 6.0 | 5.9 | 6.0 | | 5.9 | | 5.9 | | |
| | | $V_{IN} \leq V_{T-} - \text{Min}$ $I_{OH} = -2\text{ mA}$ $I_{OL} = -2.6\text{ mA}$ | 4.5 | 4.18 | 4.31 | | 4.13 | | 4.08 | | |
| | | | 6.0 | 5.68 | 5.80 | | 5.63 | | 5.58 | | |
| V_{OL} | Low-Level Output Voltage | $V_{IN} = V_{T-} + \text{Max}$ $I_{OL} = 20\text{ }\mu\text{A}$ | 2.0 | - | 0.0 | 0.1 | - | 0.1 | - | 0.1 | V |
| | | | 3.0 | - | 0.0 | 0.1 | - | 0.1 | - | 0.1 | |
| | | | 4.5 | - | 0.0 | 0.1 | - | 0.1 | - | 0.1 | |
| | | | 6.0 | - | 0.0 | 0.1 | - | 0.1 | - | 0.1 | |
| | | $V_{IN} = V_{T+}$ or V_{LH} $I_{OL} = 2\text{ mA}$ $I_{OL} = 2.6\text{ mA}$ | 4.5 | - | 0.17 | 0.26 | - | 0.33 | - | 0.40 | |
| | | | 6.0 | - | 0.18 | 0.26 | - | 0.33 | - | 0.40 | |
| I_{IN} | Input Leakage Current | $V_{IN} = 6.0\text{ V or GND}$ | 6.0 | - | - | ± 0.1 | - | ± 1.0 | - | ± 1.0 | μA |
| I_{CC} | Quiescent Supply Current | $V_{IN} = V_{CC}$ or GND | 6.0 | - | - | 1.0 | - | 10 | - | 40 | μA |

影響を受ける部品の一覧:

注: 標準の部品番号(既製品)のみが部品一覧に記載されます。本 PCN に影響を受けるカスタム 部品は、PCN メールの顧客の特定の PCN の付属文書、または PCN カスタマイズポータルに記載されています。

MC74HC1G00DFT1G

MC74HC1G04DFT2G

MC74HC1G32DFT1G

MC74HC1G00DFT2G

MC74HC1G08DFT1G

MC74HC1G32DFT2G

MC74HC1G02DFT2G

MC74HC1G08DFT2G

MC74HC1GU04DFT1G

MC74HC1G04DFT1G

MC74HC1G14DFT1G

MC74HC1GU04DFT2G

MC74HC1G14DFT2G